

1

## LEGACY KEYBOARD SUPPORT SYSTEM

This application is a continuation-in-part of provisional patent application No.

5 \_\_\_\_\_, filed July 14, 2000.

### BACKGROUND

10 Thin Client and Windows Based Terminal (WBT) systems are envisioned as a replacement for distributed computing systems in which a full-function PC operates on every desktop in the enterprise. While distributed systems may be networked to share data, storage, peripheral functions and some kinds of application programs, substantial stand-alone computing capability resides in each user's individual machine. Often this includes gigabytes of hard drive storage, diskette driver, CD-ROM and DVD ROM or other portable mass storage readers, and even portable mass storage writers. Thin Client and WBT systems contemplate a client-server architecture in which client units are PC's with fast processors and ample RAM, but without on-board permanent storage or input-output devices other than a keyboard, a mouse and a connection to a server or servers.

15 In addition to replacing networks of self-sufficient PC's, thin client networks can replace terminal-based systems. Many enterprises depending on centralized mainframe or midrange computers elect to replace hardware terminals with more flexible PCs on user desktops. Through use of emulation programs residing on a desktop PC or a connected server, the central computer communicates with the desktop units via the same I/O signals used with dedicated terminals. The remote user, meanwhile, has the flexibility of switching between the hosted application and locally stored or server-based personal productivity software, such as word processors, personal information managers or spreadsheet applications.

25  
30  
35

1 The current generation of IBM system-compatible terminal emulation PC hardware  
utilizes the PC architecture and an operating system designed to work with PC keyboards with  
101 to 104 keys, whereas most IBM Mainframe and Midrange terminals are equipped with 122-  
5 key keyboards. Some users prefer the 122-key keyboard for continuity and simplicity of  
transition, thus maintaining productivity. However, the 122-key keyboard is not supported by the  
popular Windows operating systems, Windows 95, 98, NT, CE and 2000, prevalent in PC-based  
10 systems. The conventional approach is to support the 122-key keyboard directly from the  
emulation program at the application layer, bypassing the operating system layer. This approach  
requires the emulation program to be on the local PC, which is attached to the keyboard. The  
improved design of the present invention places, on the local PC, keyboard driver and filter files  
that convert the unsupported keyboard signals into a form recognized by the operating system.  
The operating system then transmits keystroke information to the emulator program, whether it is  
on the local PC or on a remote server.

## 20 SUMMARY OF THE INVENTION

25 The present invention is addressed to the use of thin client or WBT systems in the  
terminal emulation environment. If a mainframe-terminal system is replaced with a client-server  
configuration, it is often desirable to make the changes as transparent as possible to the users.  
The former terminal unit, usually a monitor, control box and keyboard, is replaced by the  
30 monitor, logic unit and keyboard of the new unit. For the many whose legacy system terminals  
included a 122-key keyboard, implementation of a 122-key keyboard in the new system eases the  
transition.

1 The standard PC's and operating systems used in thin client and WBT systems are  
configured for 101-key keyboards, and although a 122-key keyboard can be plugged in, the  
operating system will ignore the scan code signals from unsupported keys. Corresponding  
5 keystrokes are not passed to the application program, resulting in dysfunction.

The present invention provides a solution by tricking the operating system into  
recognizing signals from the unsupported keys. The operating system's keyboard driver is  
superseded by a keyboard driver capable of processing all the scan codes from a 122-key  
10 keyboard. The driver transmits the scan codes to a filter, which passes on the standard scan codes  
and converts each non-standard scan code into a unique combination of scan codes representing  
combinations of 101-key keystrokes recognized by the operating system. A keyboard map  
accompanying the emulator then converts standard and combination keystroke codes from the  
operating system into the proper character or command codes for the application program.

## 20 **BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1 is the keyboard layout for a standard 101-key PC keyboard.

Figure 2 is the keyboard layout for an IBM 3270 122-key keyboard.

Figure 3 is the keyboard layout for an IBM 5250 keyboard for use with the AS/400 and I-  
25 Series minicomputer systems.

Figure 4 is a scan code table for a 122-key keyboard in one embodiment of the invention.

Figure 5 is a 122-key keyboard layout with each key uniquely designated.

Figure 6 is a table showing the keyboard mapping of a 3270-style keyboard.

Figure 7 is a table showing the keyboard mapping of a 5250-style keyboard.

## DETAILED DESCRIPTION

Modern keyboards output scan codes each time a key is pressed. Circuitry within the keyboard senses key depression and an on-board microprocessor generates a unique hexadecimal code on the output line corresponding to the location of the struck key. One code is generated when the key is pressed (the make code) and a different code is generated when the key is released (the break code). Make codes are necessary for all keys while break codes are essential only for modifier keys such as Shift, Control and Alt. Scan codes are converted by the terminal logic unit software to the characters, modifiers (Left Shift, Right Shift, Left Control, Right Control, Left Alt, Right Alt) or functions (e.g. Print, Help, Clear, Play, etc.) inscribed on the key. Some keyboards offer optional sets of scan codes selectable by the user, but the code for each key is always known.

The port on a terminal logic unit to which the keyboard is attached has a driver (which may be software or firmware) that recognizes and converts the incoming scan codes to either American Standard Code for Information Interchange (ASCII) or Extended Binary Coded Decimal Interchange Code (EBCDIC) characters. The ASCII and EBCDIC codes are then read as input data by the application program. When the terminal configuration is replaced by an emulation configuration, a personal computer sits on the desktop. The keyboard communicates with the personal computer, which must capture the keystrokes and send them to the emulator application program. The emulator may reside on the personal computer and communicate with the mainframe over a network, or the emulator may reside on a server and communicate with both the mainframe and one or more personal-computer-terminals over networks.

A number of different configurations of terminal emulation systems are possible, with varying equipment specifications, operating systems, network architectures and application

1 programs. Many of these employ standard or modified PC units running one of the Microsoft  
Windows operating systems. One particularly efficient configuration is the thin client system, in  
which the local desktop unit is a minimally-configured PC having, for example, a 200 MHz  
5 processor, 64 Mb RAM, a flash memory of 8 – 16 Mb, standard ports (serial, parallel, USB and  
audio) and an ethernet connection to a server, which is in turn networked to the mainframe. The  
operating system on the PC is preferably Windows CE, while the server operating system may be  
10 Windows NT TS (Terminal Server), Windows 2000 Server, Citrix Winframe or Citrix  
Metaframe. The emulation software, an application program, may reside on the desktop unit or  
on the server, but would be most efficient on the server. While persons of ordinary skill in the art  
will readily grasp that many variants of equipment configuration, network architecture and  
operating system software are possible, the invention will be illustrated using this thin client  
configuration.

20 The standard PC running Windows CE is designed to work with a 101-key keyboard. In  
terminal emulation, however, it is desirable to attach the same type of keyboard used with the  
dedicated terminal, for consistency and ease of transition. Most of the popular mainframe and  
midrange systems, such as the IBM S/390 Mainframe or the IBM System 3/x or AS/400  
midrange computers, use 122-key keyboards.

25 A typical 101-key keyboard is shown in Figure 1, and two common versions of 122-key  
keyboards are shown in Figures 2 and 3. The 122-key keyboard is equipped with 24 Function  
keys while the PC 101 keyboard has only twelve. The 122- key keyboard also has two columns  
30 of keys to the left of the typewriter area, which are IBM host-specific function and editing keys.  
One embodiment of the invention uses a 122- key keyboard based on an IBM design dating back  
to the early 1980s and introduced with the 3270/PC for use with mainframe host computers. See  
35 Figure 2. This design is a hybrid with the output of most keys being identical to a PC keyboard.

1 Only 22 of the keys output unique scan codes, namely Function keys 13 to 24, 8 of the 10 keys  
on the left side of the keyboard, the key > < directly to the left of the Z key and the key  
immediately to the right of the Back Space key. This type of keyboard is supported by the  
5 Microsoft keyboard drivers in MS DOS, Windows 3X, and OS/2 Operating Systems but is not  
supported by the Microsoft keyboard drivers in Windows 95, 98, NT, CE or 2000.

10 A representation of a 122-key keyboard, with each key uniquely numbered for  
identification, is shown in Figure 4. The scan codes for the 3270/PC keyboard keys, as provided  
by the manufacturer, are shown with their corresponding key identifiers in Figure 5.

15 In most thin client terminal emulation systems adapted to a 122-key keyboard, a new  
keyboard driver program, written in a conventional manner, supersedes the keyboard driver that  
comes with the operating system software. The driver intercepts every scan code before it is  
processed by the operating system and directs it to the emulator application, which is  
programmed to recognize the scan codes and process them for communication to the mainframe  
20 as ASCII or EBCDIC data. This driver also passes to the operating system standard scan codes,  
i.e., those that are supported by the operating system, along with Windows Virtual Key codes  
(VK codes) corresponding to the scan codes, just as though they had been processed by the  
originally-supplied keyboard driver. The operating system, performing in a routine manner,  
25 transmits the VK codes to the thin terminal protocol agent software, which communicates them  
to the server.

30 This conventional approach to thin client terminal emulation allows server-based  
Windows applications to be run from the desktop. If the user inadvertently hits an unsupported  
key, it is ignored. The disadvantage is that the emulator application must be present on the  
desktop unit to process the keyboard input, and cannot be run from the server to which the unit is  
35 networked.

1           The present invention solves this problem with a combination of a keyboard driver and a  
filter. As in the conventional approach, a replacement keyboard driver intercepts all scan codes  
as they arrive from the keyboard. Standard scan codes, with associated VK codes, are passed to  
5 the operating system. Instead of sending the scan codes to the emulator application for  
recognition of the nonstandard scan codes, however, the scan codes are sent to a filter. Using a  
table look-up, the filter converts the nonstandard scan code to a combination of modifiers and  
standard 101 key codes, and passes the modified scan codes and associated modified VK codes  
10 to the operating system.

For example, the F14 key on the 122-key keyboard is a nonstandard key. In the filter, this  
key's scan code is converted to the supported scan codes for {Shift Down, F2, Shift Up} and  
sent, along with the VK codes for {Shift Down, F2, Shift Up}, to the operating system. The  
designated modified scan codes for the nonstandard keys of the 3270/PC keyboard of the instant  
embodiment are found at Figure 6.

20           The operating system outputs the standard and modified VK codes. These can be directed  
to a local emulator application program, just as in conventional thin client terminal emulation,  
for conversion to communicate with the mainframe. Figure 6 provides a keyboard map that can  
be associated in a conventional manner with the emulator software.

25           Alternatively, the standard and modified VK codes can be passed to the thin client  
protocol agent software and then communicated to a server. The server may host the emulator  
application software and connect to the mainframe, or may connect to a separate emulator server  
30 in turn connected to the mainframe. Of course, the keyboard map file must be associated with the  
emulation software wherever it is located. In this configuration, multiple operators may use a  
single copy of the emulator application software, enjoying the benefit of thin client system  
35 design. Server-hosted emulator application software cannot work in the conventional thin client

1 terminal emulation arrangement because the Windows operating system on the server is designed  
to accept and transmit only VK codes as keyboard input signals. Thus, there is no way to  
communicate the raw scan codes to the emulator application through a network, and that  
5 emulator must reside on the desktop where it can intercept scan codes for direct processing.

The foregoing description uses a particular keyboard and operating system combination  
as an example, but it may readily be seen that many variations within the scope of the invention  
are available. One example is implementation of the IBM 5250-type keyboard, a 122-key  
10 keyboard commonly used with the AS/400 and I-Series midrange computers. Figure 3 shows the  
5250 keyboard layout, and Figure 6 is a keyboard mapping file (showing the combinations for  
modified scan codes and modified VK codes) that may be used for the nonstandard keys.

Additionally, other local operating systems may be selected instead of Windows  
CE, and these do not necessarily have to be Windows-based. Any terminal emulation system in  
which an operating system that does not support all the scan codes from the keyboard must  
convert scan codes to internal key codes for use by networked applications will benefit from this  
invention. Nor do the illustrated modified scan codes constitute the only workable substitutes for  
nonstandard scan codes. Numerous alterations and modifications of the structure herein disclosed  
will suggest themselves to those skilled in the art. All such modifications which do not depart from  
25 the spirit of the invention are intended to be included within the scope of the appended claims.